

Attorney's Docket No.:06618-760001

Amendment to the Claims:

This listing of claims replaces all prior versions, and listings, of claims in the application:

1. (Previously Presented) A receiver, comprising:
a plurality of averaged waveforms, each said averaged waveform comprising an average of a plurality of FQPSK waveforms;
a plurality of correlators, to correlate an input signal with each of said averaged waveforms of said plurality to form correlations; and
a trellis decoder using said correlations to make decisions on the transmitted signals.
2. (Previously Presented) A receiver as in claim 1, wherein said plurality of averaged waveforms each represent four FQPSK waveforms.
3. (Original) A receiver as in claim 1, further comprising an input filter which filters an input signal.
4. (Previously Presented) A receiver as in claim 1, further comprising a demodulator, receiving an input signal, and producing demodulated complex signals.

Attorney's Docket No.: 06618-760001

5. (Previously Presented) A receiver as in claim 4, wherein said demodulated complex signals include an in-phase signal and a quadrature signal component.

6. (Previously Presented) A receiver as in claim 2, wherein there are four of said correlators to correlate said FQPSK waveforms.

7. (Previously Presented) A receiver as in claim 1, wherein each of said plurality of averaged waveforms include a plurality of basic FQPSK waveforms which have similar characteristics.

8. (Previously Presented) A receiver as in claim 7, wherein each averaged waveform comprised a combination average of four FQPSK waveforms.

9. (Previously Presented) A method, comprising:
obtaining a plurality of basic waveforms which represent trellis waveforms for FQPSK or FQPSK-B;
averaging groups of said plurality of waveforms to form averaged waveforms, wherein a number of said averaged waveforms is less than a number of said plurality of waveforms; and

Attorney's Docket No.: 06618-760001

correlating an FQPSK-B input signal against said averaged waveforms to form a group of signals to be processed by a trellis decoder.

10. (Original) A method as in claim 9, wherein said averaging groups comprises averaging four of said FQPSK-B waveforms to form each averaged waveforms.

11. (Original) A method as in claim 9, further comprising filtering an input signal, and wherein said correlating comprises correlating against a filtered input signal.

12. (Previously Presented) A method as in claim 9, further comprising producing demodulated signals from input signals and a set of correlation from said demodulated signals.

13. (Previously Presented) A method as in claim 12, wherein said demodulated signals include an in-phase signal and a quadrature signal.

14. (Previously Presented) A method as in claim 9, wherein said correlating comprises using four of said

Attorney's Docket No.: 06618-760001

correlators to correlated the demodulated inphase and quadrature input signal with said FQPSK-B waveforms.

15. (Original) A method as in claim 9, wherein said plurality of averaged waveforms include a plurality of waveforms which have similar characteristics.

16. (Original) A method as in claim 9, wherein each averaged waveforms comprise a combination of four FQPSK waveforms.

17. (Currently Amended) A receiver, comprising:
a filter element, receiving an input FQPSK-B signal and producing a filtered FQPSK-B signal; and
a Viterbi Algorithm receiver, producing demodulated signals based on said FQPSK-B input signals, wherein said Viterbi Algorithm receiver compares said filtered FQPSK-B signal with a plurality of averaged signals.

18. (Cancelled)

Attorney's Docket No.: 06618-760001

19. (Original) A method of receiving an FQPSK-B signal, comprising:

- obtaining a plurality of basic FQPSK-B signals associated with modulation of an FQPSK-B signal;
- averaging said plurality of basic FQPSK-B signals to form a plurality of averaged signals; and
- comparing an input coded FQPSK-B signal with said plurality of averaged signals to carry out the modulation.

20. (Original) A method as in claim 19, wherein there are 16 of said basic FQPSK-B signals, and wherein there are four of said averaged signals.

21. (Previously Presented) A receiver as in claim 1, wherein said FQPSK waveform are FQPSK or FQPSK-B, waveforms.